

Sheet1

Model	Nominal Capacity (mAh)	Positive Electrode Material	Negative Electrode Material	Nominal (Rated) Voltage (V)	Weight (g)	Diameter (mm)	Height (mm)	Continuous Max Discharge Current (A)	Features
US18650VTC4	2,1	NCM	Gr	3,6	45	φ18	65	30	power
US18650VTC4A	2,1	NCM	Gr	3,7	46,8	φ18	65	35	power
US18650VTC5	2,6	NCA	Gr	3,6	44,3	φ18	65	30	power
US18650VTC5A	2,6	NCA	Gr, SiO	3,6	47,1	φ18	65	35	power
US18650VTC5D	2,8	NCA	Gr, SiO	3,6	46,7	φ18	65	35	power
US18650VTC6	3,12	NCA	Gr, SiO	3,6	46,6	φ18	65	30	power
US18650VC7	3,5	NCA	Gr, SiO	3,6	47,2	φ18	65	8	runtime
US18650FTC1	1,1	LFP	Gr	3,2	38,8	φ18	65	20	life, safety
US21700VTC6A	4,1	NCA	Gr, SiO	3,6	67,5	φ21	70	40	power
US26650FTC1A	3	LFP	Gr	3,2	84	φ26	66	25	life, safety

<https://www.murata.com/en-global/products/batteries/cylindrical>